



NON-FLICKER



RHINO 69K

SERIES

IQL



INDUSTRIAL, FOOD, FARMING & REFRIGERATION LIGHTING





TECHNICAL

Body	316 SS, IPC/PMMA Material
Colour Temperature	5000K
Average LED and Control Gear Life	>78,000 hrs (L70/Ta25c)
Beam Angle	120° degrees
Efficacy	140Lm/W
CRI	> 80
Max Junction Temperature	150C
Cooling	Conduction, Convection
Operating Range Tc	-20°C – 40°C
Thermal Management	Aluminium Heatsink

ELECTRICAL

Power Supply	Non-Flicker LED Driver
Protection	Over Voltage, Short Circuit and Over Temperature
Power Factor:	> 0.96
Total Harmonic Distortion (THD)	<15%
Ingress Protection Rating:	IP69K (IP67)
Impact Rating	IK10
Certification	RCM, EMC, CE, Meets International and Food Safety (IFS), BRC & HACCP
Warranty	3 Years



ORDER CODES

Model	Wattage	Light Colour	Lumens	Weight	Size (in mm)	
					A	B
RWP69K-600	20 watts	5,000K	2,800Lm	1.9kg	600	70
RWP69K-1200	36 watts	5,000K	5,600Lm	3.3kg	1200	70



SMARTER LIGHTING SOLUTIONS
IQ Lighting Australia
 6/24 Yalgar Rd, Kirrawee NSW 2232
www.iqlighting.com.au
 1300 475 444

Technical Data sheets available on request. Model appearance may vary.
 July 2020 specifications are subject to change without prior notice.